


ND Type 25.4 x 22.1 mm Oven Controlled Crystal Oscillator

FEATURE

- Dimension 25.4 x 22.1 x 11.0 mm typical.
- SC Cut Crystal.


TYPICAL APPLICATION

- SDH/SONET, Telecommunication base station
- Test and measurement equipment
- Synthesizer, Digital switch, Reference Timing Circuit



RoHS Compliant

DIMENSION



ELECTRICAL SPECIFICATION

Parameter	Min.	Typ.	Max.	Unit	Test Condition & Notes
Output					
Frequency	—	10	—	MHz	Available frequency range is from 5MHz to 40MHz. Standard frequencies are 10, 12.8, 15.36, 16.384, 19.2, 20 and 25MHz.
Waveform	—	Rectangular	—		Sine wave output is available. Consult factory for more information.
Level	—	HCMOS	—		
"1" Level	+2.4	+3.3	—	V	
"0" Level	—	—	+0.4		
Load	—	15	—	pF	
Duty cycle	45	50	55	%	@ +1.4V
Spurious	—	—	-60	dBc	
Frequency Stability					
Ambient	-10	—	+10	ppb	0°C to +70°C, referenced to +25°C Refer to Freq. Stability Vs Temp. Range table.
Aging	-0.5	—	+0.5	ppb	Per day, at time of shipment
Daily	-0.5	—	+0.5	ppb	after 30 days
Yearly	-50	—	+50	ppb	
10 years	-0.4	—	+0.4	ppm	
Voltage	-0.5	—	+0.5	ppb	±5% Change
Warm-up	-10	—	+10	ppb	In 2 minutes @ +25°C, referenced to 1 hour
Phase Noise	—	—	-115	dBc/Hz	@ 10 Hz
	—	—	-130		@ 100 Hz
	—	—	-140		@ 1 kHz
	—	—	-150		@ 10 kHz
Electrical Frequency Adjustment					
Range	—	—	-0.5	ppm	VCO @ 0 V
Control	+0.5	—	—	ppm	VCO @ +2.8 V
Slope	—	Positive	—	V	
Input impedance	100	—	—	kΩ	
Input Power					
Voltage	3.135	3.3	3.465	V	5.0V input voltage is available. Consult factory for control voltage and output level.
Current	—	—	1000	mA	@ turn on
Steady state	—	—	1.2	W	@ +25°C
Reference Voltage					
Voltage	2.7	2.8	2.9	V	
Load	9	—	—	kΩ	

FREQ. STABILITY vs. TEMP. RANGE

Temp. (°C)	ppb	±5	±10	±20
0 ~ +70		○	○	○
-30 ~ +70		△	○	○
-40 ~ +85		△	○	○

* ○: Available △: Conditional X: Not available

Note: not all combination of options are available. Other specifications may be available upon request.

Specifications subject to change without notice.